

**Environmental Health & Sanitation Chemicals** 

## echnical Data



# **BRUTE FORCE 13**



**DEGREASER** 

#### DESCRIPTION

This powerful degreaser works where others fail. Formulated with thirteen different ingredients for extremely tough jobs that require extra strength.

Concentrated, this product can be diluted with up to 100 parts water for greatest economy. This product may be used for dip tank degreasing and corrosion protection. Rust preventatives form a corrosion inhibiting coating when diluted degreaser is not rinsed from metal surfaces. Superior grease and soil penetration and retention allow this degreaser to be used in many ways.

#### SPECIFICATIONS

SI ECHICATIONS	
Fragrance Ch	erry Almond
Color	Green
Foaming	
Biodegradability	
Emulsification	
Shelf Life	
Freeze/thaw stability	3 cycles
Rinsability	. Very Good
Viscosity	
Flash Point	None
pH	13.2

#### **USES / BENEFITS**

- Non-flammable, noncorrosive, biodegradable
- Contains rust preventatives
- Excellent for steam cleaning and pressure washers
- May be used in dip tanks. hot or cold
- Removes rubber tire marks
- Use manually, or in automatic scrubbers

#### **PRECAUTIONS**

Keep Out Of Reach Of Children. For industrial and institutional use only by trained personnel.

Non-flammable, contains no chlorinated solvents. WARNING: Skin and eye irritant. Harmful if swallowed. Contains free hydroxide. When using, wear face mask and/or goggles, protective gloves and clothing. FIRST AID: In case of accidental ingestion, immediately drink large volumes of water or milk - then attempt to drink undiluted vinegar or lemon juice. In case of eye or skin contact, wash with plenty of cold running water. IN ANY CASÉ, GET MEDICĂL ATTENTION.

### **DIRECTIONS FOR USE**

For general maintenance, floors, walls, machinery, engines, conveyors, ducts, kitchen ovens and grills, air filters, shower tile, concrete, terrazzo, white side wall tires.

- Light soil ...... 1 to 100
- Medium soil ...... 1 to 50 •Heavy soil ...... 1 to 25
- Very heavy soil .......... 1 to 5 DIP TANK DEGREASING AND CORROSION PROTECTION: Use undiluted or dilute up to a 1 to 15 dilution.

SPRAY. STEAM, PRESSURE WASHING: Dilute with from 30-50 parts water. AUTOMATIC SCRUBBERS: Dilute with 40-60 parts water.

CONTAINS 13 SOIL REMOVAL ENHANCING INGREDIENTS

**"Exclusive Distributors Of** 



