



Environmental Health & Sanitation Chemicals

Technical Data



GEAR LUBE



OPEN GEAR LUBRICANT

DESCRIPTION

This product is a solid film, highly viscous lubricant for use on gears, chains, cables, wire ropes, sprockets, industrial machinery, and heavy construction equipment. Protects against rust and corrosion by repelling water from surfaces. Excellent stretching characteristics allow surfaces to be completely covered with lubricant extending life of machinery and reducing down time and maintenance. Reduces noise and protects gears in case of excessive loads. Effective temperature range of +20°F to +175°F.

USES / BENEFITS

USE FOR:

- open gears
- chains
- cables
- wire ropes

PRECAUTIONS

Keep Out Of Reach Of Children

DIRECTIONS FOR USE

Shake can well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to insure adequate lubrication. Reapply as needed to lubricate and protect equipment. After spraying, turn can upside down and spray until nozzle is clear.

SPECIFICATIONS

Color Black
Flash Point 122°F

EXCELLENCE
SINCE
1964

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 • www.northwoodstm.com

