



Environmental Health & Sanitation Chemicals

Technical Data

TITANIUM

EXTREME DURABILITY FLOOR FINISH

DESCRIPTION

Every once in awhile, something truly unique comes along. This is certainly the case with our latest innovation in floor finish. Titanium is the ultimate in high gloss, extreme durability, extra long wear, and ultra low maintenance. This makes it the ideal choice for facilities who want great looking floors - but don't have the time to get them through traditional means. With a name like Titanium - you know it has to be good!

SPECIFICATIONS

Color	Liquid White
Color Dried	Crystal Clear
Coverage	3,000 sq. ft. gal.
Dry Time	20 - 30 minutes
Gloss (one coat)	80 - 85
Gloss (two coat)	85 - 90
Total Solids	30%
Heel Mark Resistance ...	Excellent
Leveling	Excellent
pH	8.1 - 8.9
Powdering Resistance ...	Excellent
Recoat	Excellent
Specific Gravity	1.026
Recommended Coats	4 - 6
Top Scrub	2 - 3
Shelf Life	1 year

USES / BENEFITS

- Resilient tile
- Terrazzo
- Marble
- Superior wearing and non-scutting.
- Self-leveling, self-sealing.
- Resists dirt embedment.
- No buffing necessary
- Black mark resistant
- Offers extreme durability
- Never yellows
- Fantastic scrub & recoat product

PRECAUTIONS

Keep Out Of Reach Of Children

**EXCELLENCE
SINCE
1964**

DIRECTIONS FOR USE

Read the entire label before using this product. Recommended for use on all types of resilient tile (vinyl composition, vinyl, linoleum) and properly sealed hard surfaces (marble, terrazzo).

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on BARE BONES label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. 4 - 5 coats of finish are recommended. Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of BEDROCK will enhance gloss and long term performance.

ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using BLUE OX. Buff or burnish the floor as desired. The use of SOLAR BURST is recommended to condition the floor and extend the time between top scrub and recoating.

INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using POWER SCRUB and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. Note: Slip resistance meets or exceeds standard, (ASTM D 2047-04) James Machine 0.5 minimum.

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 • www.northwoodstm.com

