



Environmental Health & Sanitation Chemicals

Technical Data



ASPHALT PATCH



PAVING PATCH MATERIAL

DESCRIPTION

Cracks, potholes and fault lines are the pits to fill. With "Asphalt Patch" you have an easy, durable solution for filling those annoying, unattractive craters in the pavement. This hardy sealant is made from a mix of flexible yet resilient ingredients including screened aggregate, tar and asphalt binders. It remains pliable within its container until it is applied to pavement surfaces. Even when temperatures dip as low as 15°F, it remains loose enough for easy application. Once it sets up, it keeps cracks sealed not matter how inclement the weather may get. So don't settle for just any crack sealer. Get the only product that can do the whole job.

USES / BENEFITS

- Can be used in any weather
- No primer coat is needed
- Can be used in temperatures as low as 15°F.

DIRECTIONS FOR USE

Brush dust and dirt away and fill the crack or hole with Asphalt Patch and tamp down.

SPECIFICATIONS

Color	Black
Fragrance.....	Petroleum Odor
Ready to use	yes
Specific gravity.....	1.01
Flash point.....	450°F
Stability	2 years @ 70°F

PRECAUTIONS

CAUTION: Avoid breathing vapors. Keep out of reach of children.

Use for repairing:

- Concrete
- Asphalt
- Black Top
- Stone
- Brick Roads
- Parking Areas
- Playgrounds
- Driveways

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 • www.northwoodstm.com

