



Environmental Health & Sanitation Chemicals

Technical Data

GREASE



LUBRICANT • PENETRANT • RUST PREVENTATIVE

DESCRIPTION

This new safe formulation of a high temperature liquid set up grease was designed to meet the 21st Century safety requirements for a safer earth, plus be outstanding as a non-melting grease. This product sprays out in a penetrating liquid and transforms into a cured, long lasting lubricant. Withstands heat to 500°F, moisture, salt, acids, high pressure and is rust resistant. Sprays easily into those hard to reach areas and gives lasting lubrication. Use safely on chains, winches, conveyors, gears, cables, tools, hinges, bushings, pins, levelers, rollers and your imagination can pick some more. A high pressure tackifier prolongs the superb performance for wear and operational longevity.

USES/BENEFITS

- Prolongs life of metal parts
- High shock and impact resistance
- Contains corrosion and rust inhibitors
- Exceptional adhesive cohesive and anti-wear properties

DIRECTIONS FOR USE

SHAKE WELL. Remove cap and point spray tip at area to be treated. For hard to reach areas, use long extender tube and insert in hole of valve tip. Apply in short spurts using several light coats in lieu of one heavy coat. Work parts to distribute lubricant evenly. Spray as necessary to insure full coverage.

SPECIFICATIONS

Color Red
 Specific Gravity 1.20
 Net Weight 15 ounces
 Storage Stability 1 year +

PRECAUTIONS

Keep Out Of Childrens Reach

**A Penetrating Liquid That
Forms a Non-Melt Grease!**

EXCELLENCE
SINCE
1964

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 • www.northwoodstm.com

