



Environmental Health & Sanitation Chemicals

Technical Data



LOW TEMP TERG



LOW TEMPERATURE MACHINE DISHWASHING DETERGENT

DESCRIPTION

LOW TEMP TERG is specially formulated to produce clean and sparkling tableware in Low Temperature dishmachines. LOW TEMP TERG attains excellent results in light to medium soil conditions where soft to medium water hardness conditions are available. LOW TEMP TERG is dispensed directly from the shipping container, thus eliminating messy spills and unsightly dish areas. This unique product is formulated to be dispensed through an automated injector system, assuring the lowest possible use cost. LOW TEMP TERG can be used to wash soft metals such as aluminum or pewter.

SPECIFICATIONS

Appearance Clear amber liquid
 pH 12.5
 pH of 1% solution 12.3
 Specific gravity 1.24 (10.3 lbs/gal)
 Solubility Complete and Fast
 Stability 1 Year
 Foaming Low
 Biodegradable Yes, all surfactants
 Metal Safety Safe with soft metals
 Water Hardness Tolerance:
 9 Grains Per Gallon at 0.3%
 6 Grains Per Gallon at 0.2%
 3 Grains Per Gallon at 0.1%

USES / BENEFITS

- Extremely economical
- Saves Time, Saves Money
- Deep cleans
- Leaves wares sparkling
- Biodegradable surfactants
- Excels in low temperatures
- Works even in harder water conditions
- Automatically dispensed
- No mess, no fuss
- Protects your investment
- Simple to use
- Safe on soft metals
- Contains sequestering agents

PRECAUTIONS

Keep out of reach of children
 Highly alkaline liquid. Contact with skin and eyes may cause severe irritation. Harmful if swallowed. Flood with water if splashed in eyes. Flush with water for 15 minutes and consult physician immediately. If ingested, drink large amounts of milk, milk of magnesia or gelatin, or if these are not available, drink large amounts of water. DO NOT induce vomiting. Obtain prompt medical attention.

DIRECTIONS FOR USE

This unique product is formulated to be dispensed through an automated injector system, assuring the lowest possible use cost.

Titrate with Institutional Alkalinity Test Kit. Use range is 0.1% to 0.3%, or 2 to 6 drops (each drop = .05%) using a 10 ml sample and 3 drops of Phenolphthalein Indicator. Select actual use concentration to handle water hardness and soil load.

EXCELLENCE
 SINCE
 1964

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 •• www.northwoodstm.com

