



Environmental Health & Sanitation Chemicals

Technical Data



STRIP IT

PAINT - VARNISH - GASKET & DECAL REMOVER



DESCRIPTION

Gel formulation paint remover quickly removes paint, epoxy, lacquer, decals, gaskets, shellac, enamel, varnish, labels, gasket cement, glue, carbon deposits, silicone and simulated wood paneling. Product will not run. This formula has been formerly authorized by the USDA for use in federally inspected meat and poultry plants.

USES / BENEFITS

- For use by:**
- auto dealers • paint shops
 - maintenance departments
 - engine rebuilders • factories
 - furniture refinishers
 - painters • sign builders • schools
 - motels • hotels • hospitals
 - offices

- For use on:**
- metal parts • plaster • concrete • tile • glass • ceramic • engine parts • valve seals • paint guns • paper • wood • stone
 - masonry • cylinders

DIRECTIONS FOR USE

Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

SPECIFICATIONS

Color Clear
 Specific gravity 1.20
 Net Wt. 13 ounces
 Storage Stability 1 year

PRECAUTIONS

Keep out of reach of children.

**NEW JELLED FORMULATION
 CLINGS TO VERTICAL SURFACE**

**EXCELLENCE
 SINCE
 1964**

"Exclusive Distributors Of  North Woods® Chemicals"

800.242.7694 • www.northwoodstm.com

