



Environmental Health & Sanitation Chemicals

Technical Data



TEF LUBE

LUBRICANT • PENETRANT & RUST DISSOLVER



DESCRIPTION

Tef Lube was scientifically formulated as a penetrating oil and rust dissolver containing micron size particles of Teflon and Moly. This super penetrant carries the Teflon and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed. Tef Lube is designed to be used on all dismantling jobs throughout the plant, shop, maintenance area or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints.

USES / BENEFITS

Used for loosening rusted parts and lubrication of:

- wire cable
- door hinges
- chains
- hoists
- pulleys
- cranes
- fork lifts
- sprockets
- gears
- block and tackle
- conveyors
- construction machinery
- industrial parts and locks

DIRECTIONS FOR USE

Shake well. Remove protective cap and spray holding can 6-12 inches from surface. Spray liberally, saturating joints, threads, etc. Allow to set 5-10 minutes and break out. For extremely difficult jobs, saturate, wait 5-10 minutes, then tap lightly with hammer and break.

PRECAUTIONS

Keep Out Of Reach Of Children

**CONTAINS TEFLON® & MOLY
LOOSENS NUTS & BOLTS
DISPLACES MOISTURE**

SPECIFICATIONS

Appearance Clear
Flash Point +110°F
Specific Gravity 0.80

**EXCELLENCE
SINCE
1964**

"Exclusive Distributors Of  **North Woods®** Chemicals"

800.242.7694 • www.northwoodstm.com

